

KINGFIELD CONSTRUCTION PRODUCTS



NOVATAK™ QMQ DUAL BOND™

Novatak Ionic Waterproofing System

**Non-Vulcanized Butyl Double-Sided Adhesive Tape
20% Recycled Content - Cold, Heat, & UV Resistant**

Description

QMQ Dual Bond is an extremely adhesive, double-sided, non-vulcanized butyl rubber seaming tape used for lap seams and detailing the Novatak sheet membrane. It is chemically resistant and exceptionally adhesive and has the ability to remain flexible while maintaining a water tight seam. QMQ Dual Bond requires no primer, can be applied directly to the Novatak sheet membrane, and is easily applied to the support of excavation and around penetrations as long they are clean and dry substrates.

Advantages

Features

Greater than 99% solids

Maintains excellent adhesion

Maintains flexibility

Easy workability

Superior chemical resistance

& Impervious to hydrocarbons

Benefits

Maintains volume to ensure a watertight bond.

Primer is unnecessary for fast and easy application.

Dynamically responds to movement, thermal cycling to maintain a watertight bond.

Trims cleanly & Applies and adheres in cold temperatures.

Resistant to most soil contaminants, QMQ Dual Bond retains its physical properties in the harshest environments ensuring long term effectiveness.

Applications

QMQ Dual Bond is used to seam the Novotak pre-applied waterproofing sheet membrane. It is also used at floor-to-wall and wall-to-ceiling transitions to adhere a detailing reinforcement strip of Novotak sheet membrane to the Novotak sheet membrane system.

QMQ Dual Bond Product Data

Appearance	Black
Dimensions	3.94 in. x 19.685 ft.
Thickness	40 mils (nominal)
Weight	1.41 lb. / roll
Solids Content	>99%
Storage	Keep out of direct heat. Keep dry.
Health & Safety	See MSDS

Application Procedures

Always ensure that the surface of the Novotak sheet membrane and/or detailing surface area is clean and dry before installation of QMQ Dual Bond.

Seaming the Novotak sheet waterproofing membrane:

Overlap membrane according to width of tape. Install tape onto seam leaving release paper on the tape. Use roller to firmly press tape onto the Novotak sheet membrane before pulling release paper off. Pull release paper while adhering the adjacent Novotak sheet.

Detailing the Novotak sheet waterproofing membrane:

Install tape onto surface of Novotak sheet on both the vertical and horizontal sections of the detail reinforcement Novotak sheet 2-4 inches from the edge of each horizontal edge to ensure a tight sandwich bond of the two Novotak membranes.

KINGFIELD CONSTRUCTION PRODUCTS

Minneapolis, Minnesota

www.kingfieldcp.com

TECHNICAL SUPPORT

Phone: +1 (612) 225-5167

Email: info@kingfieldcp.com

©2014 Kingfield

Printed in U.S.A.

LIMITED WARRANTY NOTICE Every reasonable effort is made to apply KINGFIELD CONSTRUCTION PRODUCTS (KCP) exacting standards both in the manufacture of our products and in the information which we issue concerning these products and their use. We warrant our products to be of good quality and will replace or, at our election, refund the purchase price of any products proved defective. Satisfactory results depend not only upon quality products, but also upon many factors beyond our control. Therefore, except for such replacement or refund, KCP MAKES NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, INCLUDING WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY, RESPECTING ITS PRODUCTS, AND KCP shall have no other liability with respect thereto. Any claim regarding product defect must be received in writing within one (1) year from the date of shipment. No claim will be considered without such written notice or after the specified time interval. User shall determine the suitability of the products for the intended use and assume all risks and liability in connection therewith. Any authorized change in the printed recommendations concerning the use of our products must bear the signature of the KCP Technical Manager.

This information and all further technical advice are based on KCP's present knowledge and experience. However, KCP assumes no liability for providing such information and advice including the extent to which such information and advice may relate to existing third party intellectual property rights, especially patent rights. In particular, KCP disclaims all CONDITIONS AND WARRANTIES, WHETHER EXPRESS OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF FITNESS FOR A PARTICULAR PURPOSE OR MERCHANTABILITY. KCP SHALL NOT BE RESPONSIBLE FOR CONSEQUENTIAL, INDIRECT OR INCIDENTAL DAMAGES (INCLUDING LOSS OF PROFITS) OF ANY KIND. KCP reserves the right to make any changes according to technological progress or further developments. It is the customer's responsibility and obligation to carefully inspect and test any incoming goods. Performance of the product(s) described herein should be verified by testing and carried out only by qualified experts. It is the sole responsibility of the customer to carry out and arrange for any such testing. Reference to trade names used by other companies is neither a recommendation, nor an endorsement of any product and does not imply that similar products could not be used.