



# BENTOTAK AB

## KINGFIELD APPLIED WATERSTOP SYSTEMS

Delayed Swell, Self-Adhesive Modified Asphalt-Bentonite Waterstop Strip



Bentotak AB is a flexible composite waterstop consisting of specially modified Asphalt and dense, high swelling Bentonite. It is designed to adhere to surfaces that cannot be mechanically penetrated and to stop water penetration from any direction. Bentotak AB's Asphalt-Bentonite compound incorporates highly concentrated Bentonite and restricts its swelling potential from 500% to 200%, increasing the density of the bentonite in contact with substrate. Bentotak AB will expand to fill voids in concrete where water has penetrated.

### APPLICATION PROCEDURE

*Bentotak AB is easy to apply and can be cut by utility knife or scissors. The surface should be clean, dust free, and dry before applying. Place Bentotak AB over the joint, around the piping or beam, or in the keyway so as to be as near as possible to the center of the concrete thickness. DO NOT STRETCH BENTOTAK AB.*

**For Concrete Construction Joints:** Place end of Bentotak AB roll in middle of joint and roll onto joint with release liner side up. Do not remove release liner during application. Sidelap strips by 2 inches. Remove release liner prior to concrete pour to prevent debris from adhering to applied waterstop strip.

**For Door & Window Surrounds:** Apply Bentotak AB to surround and remove release liner. Sidelap strips by 2 inches.

**For Ducts, PVC & Steel Piping, Sleeves, and Steel Beams:** Locate middle of concrete pour and wrap at minimum one time around penetration with a 2 inch sidelap. Side-wrap 2 times around penetration for concrete pours 18 inches or thicker.

### PACKAGING

Bentotak AB rolls are 1" x 0.2" x 16.4' (25mm x 5mm x 5m)  
4 rolls per carton (65.6 feet – 20 meters)

### STORAGE

Store in a dry location.  
Avoid contact with water prior to application.

### HEALTH & SAFETY

Bentotak AB is non-toxic and does not present any undue hazard, however gloves should be worn as skin may be irritated with prolonged contact to adhesive coating. Wash hands with soap and water after use. See SDS.

### APPLICATIONS

- Horizontal & vertical concrete construction joints
- Door & window surrounds
- Ducts, PVC & steel piping, sleeves, steel H & I-Beams

### KEY FEATURES

Self-Adhesive – Integrated adhesive asphalt compound  
Delayed Swell = Wet weather & ponding water friendly  
Non-expanding, swelling waterstop = Stress-free joints  
Suitable for wet/dry & fresh/salt water conditions

**INFO@KINGFIELDCP.COM – 612.225.5167 – WWW.KINGFIELDCP.COM**

**KINGFIELD CONSTRUCTION PRODUCTS – 20 NORTH 4TH STREET, SUITE 300, MINNEAPOLIS, MINNESOTA 55401**

The information contained herein is believed by Kingfield Construction Products to be accurate and is offered solely for the customer's consideration, investigation, and verification. Determination of suitability for use is the responsibility of the user. Kingfield's Limitations, Limited Warranty, & Disclaimer along with Standard Terms & Conditions apply. See [www.kingfieldcp.com](http://www.kingfieldcp.com) for more info. Limitations: Standard variations of mechanical properties and hydraulic properties are normal. Kingfield products are resistant to chemicals in normal soil environments, however some reagents may affect the performance of these products. A Kingfield representative should be contacted for further information to determine the suitability of use of these products in unusual soil environments. Unless otherwise stated, Kingfield products should have limited exposure to artificial UV and sunlight. Kingfield products should be protected immediately, and if applicable, backfilled or covered within seven days of installation. Disclaimer: All information, drawings and specifications are based on the latest published information at the time of printing. Kingfield reserves the right to make changes due to manufacturing improvements and engineering at any time. All physical properties are minimum average values (MAV).