

Sepa-Seal 5000- Kingfield Construction Products

SAFETY DATA SHEET (SDS)

SECTION 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name	Sepa-Seal 5000
Control Number	NS1115
Manufacturer	Kingfield Construction Products, Inc.
Address	530 North 3rd Street, Suite #230 Minneapolis, Minnesota 55401 USA
Contact Number	+1 (612) 225-5167
E-Mail	info@kingfieldcp.com
Date	October, 2013

SECTION 2 - HAZARDS IDENTIFICATION

Physical Hazards	No available information
Health Hazards	No available information
Environmental Hazards	No available information
GHS Classification	Category 3

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

Substance/Mixture	Mixture
Chemical or Common Name	Butyl Rubber Sealant

Ingredients and Contents:

Ingredients	Contents	CAS No.
Mixture of butyl rubber, inorganic filler	75-80%	N/A
Distillates (petroleum),hydrotreated light	20-25%	64742-47-8
Benzenamine,N-(1-methylethyl)	0.1-1%	768-52-5

SECTION 4 - FIRST AID MEASURES

If inhaled	May cause respiratory irritation. May cause drowsiness or dizziness.
In case of skin contact	Remove from skin and wash with water for 15 minutes. Seek medical attention if irritation or ill effects develop or persist.
In case of eye contact	Flush with water. Seek medical attention.
If swallowed	Rinse inside of mouth with water. Seek medical attention.

SECTION 5 - FIRE FIGHTING MEASURES

Suitable Extinguishing Media	Water spray, foam, dry chemical powder, carbon dioxide
Unsuitable Extinguishing Media	No available information
Specific Methods	Keep flammable materials from the fire site and extinguish using suitable media from upwind.
Protection of Fire-Fighters	Wear protective equipment

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Sawdust, sand, perlite are mixed and solidification recovery is carried out as the shape of paste.

SECTION 7 - HANDLING AND STORAGE

Handling Avoid contact to ignition source or and high-temperature materials. Avoid skin and eye contact.
Do not breathe vapor.

Storage Keep 40 F to 88 F. Protect from sunlight in a cool and well-ventilated place.
Use reasonable care and store away from oxidizing materials.Keep away ignition sources.

SECTION 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

Wear chemical resistant gloves, safety glasses and long sleeved work clothes. Wash hands after use.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance	(color) Grey, (form) Paste
Odor	Odor of hydrocarbon
Melting Temperature	No available information
Flash Point	160.8 F
Relative Density	1.41 (64 F)
Solubility	Insoluble in water
Flammability	No available information

SECTION 10 - STABILITY AND REACTIVITY

Stability	Stable under proper conditions
Reactivity	Reactive with strong oxidizing agents.
Conditions to avoid	Ignition source, flame, and high-temperature materials
Incompatible materials	Oxidizing agents

SECTION 11 - TOXICOLOGICAL INFORMATION

No available information

SECTION 12 - ECOLOGICAL INFORMATION

Harmful to aquatic life.

SECTION 13 - DISPOSAL CONSIDERATIONS

Follow laws, regulations and local rules regarding waste disposal. Offer wastes to a licensed disposal company.

SECTION 14 - TRANSPORTATION INFORMATION

Load containers without tumbling, falling, and damaging, and thoroughly prevent containers from load collapse.
Follow laws and regulations upon transportation.

CFR/DET	Not Regulated
TDG	Not Regulated
IMDG	Not Regulated

SECTION 15 - REGULATORY INFORMATION

North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components : None present or none present in regulated quantities.

SECTION 16 - OTHER INFORMATION

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.