


- FILTER FABRIC (RECOMMENDED)
- DRAIN DOME, CLAMPING RING AND BOWL
- ROUNDED DRAINAGE AGGREGATE (RECOMMENDED)
- SECURE CLAMPING RING DOWN OVER DUROFLEX FLASHING AND HYDROGEL
- DUROFLEX FLASHING
- HYDROGEL (80 MILS ABOVE AND BELOW)
- INSULATION HELD BACK FROM DRAIN (RECOMMENDED)
- K-400 OR OTHER DRAINAGE COMPOSITE SHEET
- HYDROGEL (80 MILS) PROTECTION SHEET (MANUFACTURER APPROVED)
- DEPRESS AREA AROUND DRAIN
- RECESS DRAIN BOWL FLANGE FLUSH WITH TOP OF CONCRETE

6" (MIN.)      4" (MIN.)      1/2"

 <p style="font-size: small; margin-top: 5px;">OFFICE: 612.225.5167    www.kingfieldcp.com</p>	<p><b>DRAIN (PLAZAS)</b></p> <p>HYDROGEL GEL-FLEX WATERPROOFING SYSTEM</p>	<p>DRAWING NO. :    HYD-3.02v1</p> <p>SCALE :            NOT TO SCALE</p> <p>EFFECTIVE DATE : .</p>