



PreTape D

Product Description

Basic Use: PreTape D is a seaming, detailing, and repair tape that is used for sandwich seam applications. PreTak seams and detailing patches are adhered to both sides of the tape to form a continuous and integral seal to the structure eliminating lateral water migration.

PreTape D is a double-sided thick adhesive tape formulated with an aggressive adhesive that bonds strongly to HDPE, PSA, metal, penetrations, protrusions, and detailing and repairing PreTak membranes and is protected with a release liner.

PreTape D can be used to seal seam overlaps, end laps, penetrations, details, damage to the membrane, adhere to soldier pile flanges, and more.

Composition: PreTape D is 15-mil (0.4 mm) tape comprised of a single layer of aggressive adhesive protected with a release liner.

Benefits

- Dual sided adhesive tape for high strength sandwich seams and penetration detailing.
- Forms a continuous adhesive bond to prevent lateral water migration.
- Chemical resistant - effective in most types of soils, including hydrocarbon-laden soils.
- Strong HDPE adhesive prevents seam popping due to environmental exposure.
- Easy to apply, fully-adhered, watertight adhesive seams .
- Provides a barrier to water, moisture, gas, and vapor.
- Flexible and easily applied for detailing and seaming.

Limitations

- Surfaces must be clean and dry.
- Do not leave exposed for longer than 60 days.

Technical Data

Coverages: One roll covers 164 linear feet (50 linear meters), not including overlaps or waste.

Storage and Handling: Store raised off the floor away from sun and moisture, between 40-90°F (5-32°C).

Specification Writer: Contact EPRO before writing specifications on this product. PreTak HDPE Pre-Applied Waterproofing System should be reviewed in order to meet project specific site conditions.

Installation

Preparation: Please refer to manufacturer's specifications for substrate requirements. Rolls should be inspected for cosmetic damage prior to application.

Application: Please refer to manufacturer's specifications.

Substrate Preparation: Wipe substrates to receive PreTape D clean to remove any dirt, dust, or moisture. Clean the surface of penetrations or protrusions with a wire brush to remove dirt, dust, rust, and loose particles.

Installation: Unroll the tape and adhere to the exposed PSA surface of the PreTak membrane or exposed surface of the penetration. The release liner protected top surface of the tape should face toward the lap seam or detail patch. Line the top sheet or patch over the tape and adhere to the tape by removing the release liner and use a heavy roller to maximize adhesion. Ensure the plastic release liner is removed from all areas of the applied PreTape D prior to the concrete pour.

Availability and Packaging

Contact EPRO sales representative for local distributors or authorized applicators (www.eproinc.com).

Roll Size: 15 mil (0.4 mm), 3.15" x 164' (80 mm x 50 m), 6 lbs (2.7 kg)
Box Size: 12 rolls, 72 lbs (32.4 kg)

Warranty

Limited Warranty: EPRO Services, Inc. believes to the best of its knowledge that performance tables are accurate and reliable. EPRO warrants this product to be free from defects. EPRO makes no other warranties with respect to this product, express or implied, including without limitation the implied warranties of MERCHANTABILITY OR FITNESS FOR PARTICULAR PURPOSE. EPRO's liability shall be limited in all events to supplying sufficient product to retreat the specific areas to which defective product has been applied. EPRO shall have no other liability, including liability for incidental or resultant damages, whether due to breach of warranty or negligence. This warranty may not be modified or extended by representatives of EPRO or its distributors.

Equipment

Seaming: 4" heavy seam roller.

Technical Services and Information

Complete technical services and information are available by contacting EPRO at 800.882.1896 or www.eproinc.com.

This product was formally known as Pre-tak Tape DS by Kingfield Construction Products.